



Einschraubverschraubung, L-Form 90°, SAE/MS, O-Ring, einstellbar  
**CSLA**



**Verbindung zölliger Rohre mit zylindrischen SAE/MS Innengewinden**

Bestellnummer	Rohr AD D		Zylindrisches Gewinde T(U)	d min.	Schlüsselweite						A	B	ℓ	ℓ <sub>1</sub>	L	L <sub>1</sub>	K	O-Ring Einheitsgrößennummer
	Zoll	mm			h		H		H <sub>1</sub>									
					Zoll	mm	Zoll	mm	Zoll	mm								
CSLA 4 · 4U	1/4	6,35	7/16-20	4,82	1/2	12,70	9/16	14,28	9/16	14,28	15,24	17,78	21,08	9,90	28,44	28,44	16,51	-904
CSLA 4 · 6U	1/4	6,35	9/16-18	4,82	5/8	15,87	9/16	14,28	11/16	17,46	15,24	17,78	23,11	11,17	30,48	32,25	20,06	-906
CSLA 5 · 5U	5/16	7,93	1/2-20	5,84	9/16	14,28	5/8	15,87	5/8	15,87	16,25	18,54	22,86	9,90	30,22	29,46	18,28	-905
CSLA 6 · 6U	3/8	9,52	9/16-18	7,11	5/8	15,87	11/16	17,46	11/16	17,46	16,76	19,30	24,63	11,17	32,00	32,25	20,06	-906
CSLA 6 · 8U	3/8	9,52	3/4-16	7,11	13/16	20,63	11/16	17,46	7/8	22,22	16,76	19,30	27,43	12,70	34,79	37,84	25,65	-908
CSLA 8 · 8U	1/2	12,70	3/4-16	10,41	13/16	20,63	7/8	22,22	7/8	22,22	22,86	21,84	27,43	12,70	37,59	37,84	25,65	-908
CSLA 10 · 10U	5/8	15,87	7/8-14	12,70	1	25,40	1	25,40	1	25,40	24,38	21,84	29,46	14,22	39,62	43,43	29,46	-910
CSLA 12 · 12U	3/4	19,05	1-1/16-12	15,74	1-1/16	26,98	1-1/8	28,57	1-1/4	31,75	24,38	21,84	31,24	16,76	41,40	48,76	36,57	-912
CSLA 14 · 14U	7/8	22,22	1-3/16-12	18,28	1-1/4	31,75	1-1/4	31,75	1-3/8	34,92	25,90	21,84	33,02	16,76	43,18	50,54	40,38	-914
CSLA 16 · 16U	1	25,40	1-5/16-12	22,35	1-3/8	34,92	1-1/2	38,10	1-1/2	38,10	31,24	26,41	38,35	16,76	50,54	53,59	43,94	-916
CSLA 20 · 20U	1-1/4	31,75	1-5/8-12	27,68	1-11/16	42,86	1-7/8	47,62	1-7/8	47,62	41,14	38,86	45,72	16,76	67,81	58,16	54,86	-920
CSLA 24 · 24U	1-1/2	38,10	1-7/8-12	34,03	2	50,80	2-1/4	57,15	2-1/8	53,97	50,03	45,21	50,80	16,76	77,97	60,45	62,23	-924
CSLA 32 · 32U	2	50,80	2-1/2-12	45,97	2-3/4	69,85	3	76,20	2-3/4	69,85	67,56	62,73	69,85	16,76	107,18	71,62	80,26	-932

Einschraubverschraubung, L-Form, SAE/MS, O-Ring, einstellbar  
**CSLA**



**Verbindung metrischer Rohre mit zylindrischen ISO Innengewinden**

Bestellnummer	Rohr AD D	T G(PF)	d min.	Schlüsselweite			A	B	ℓ	ℓ <sub>1</sub>	L	L <sub>1</sub>	K	O-Ring Einheitsgrößennummer
				h	h <sub>1</sub>	H								
CSLA 6M · 2G	6	1/8	4,0	12,7	14,2	14	15,3	17,7	19,6	8,1	27,0	26,4	15,0	-002*
CSLA 6M · 4G	6	1/4	4,8	15,8	19,1	14	15,3	17,7	21,6	9,1	29,0	32,3	20,2	-111
CSLA 8M · 2G	8	1/8	4,0	14,2	14,2	16	16,2	18,6	21,3	8,1	28,8	27,4	15,0	-002*
CSLA 8M · 4G	8	1/4	5,9	15,8	19,1	16	16,2	18,6	22,4	9,1	29,9	32,2	20,2	-111
CSLA 8M · 6G	8	3/8	6,3	20,5	20,6	16	16,2	18,6	25,2	9,4	32,7	37,1	26,4	113
CSLA 10M · 4G	10	1/4	5,9	20,6	19,1	19	17,2	19,5	25,9	9,1	33,5	35,0	20,2	-111
CSLA 10M · 6G	10	3/8	7,9	20,6	22,2	19	17,2	19,5	25,9	9,4	33,5	37,1	23,5	-113
CSLA 10M · 8G	10	1/2	7,9	24,0	24,0	19	17,2	19,5	27,9	13,0	35,5	43,3	32,0	P18
CSLA 12M · 4G	12	1/4	5,9	20,6	19,1	22	22,8	22,0	25,9	9,1	36,0	35,0	20,2	-111
CSLA 12M · 6G	12	3/8	7,9	20,6	22,2	22	22,8	22,0	25,9	9,4	36,0	37,1	23,5	-113
CSLA 12M · 8G	12	1/2	9,5	23,8	26,9	22	22,8	22,0	27,9	13,0	38,0	43,4	34,5	-1298*
CSLA 12M · 12G	12	3/4	9,5	26,9	34,9	22	22,8	22,0	29,7	13,0	39,8	48,8	43,5	-119
CSLA 16M · 8G	16	1/2	12,7	24,0	24,0	25	24,4	22,0	27,9	13	38,0	43,4	32,0	P18
CSLA 25M · 12G	25	3/4	21,8	34,5	34,9	38	31,3	26,5	36,8	13	49,0	52,6	41,1	119

\* Keine einheitliche O-Ring Größe

Alle Maße in Millimetern, sofern nicht anders angegeben. Maße nur zur Information, Änderungen vorbehalten.